

Quality products

ISOHEAT[®]

Capillary pipe - thermostat

series MiL-CST



Description:

The particularly robust electromechanical surface thermostat is applicable everywhere simple continual product temperature is required. The transparent cover protects against unintentional adjustments of the temperature settings.

Features:

- stable polycarbonate housing with clear cover
- indicator lamps for mains and operation
- temperature setting visible from outside
- direct connection from mains and heating possible
- switched power up to 16 A
- fastening screw 3 x M20
- length capillary pipe ca. 2 m

Technical data

MiL-CST

nominal voltage	230 V AC
switch power	3650 W
switch current	16 A
temperature range	see order data
length capillary pipe	ca. 2 m
capillary pipe material	CU
switch difference	2,5 %
protection class	I
protection type	IP 65
fastening screw	3 x M20
dimensions	170 x 140 x 100 x mm (w x h x d)

Order data

type	temperature range	order-no.
MiL-CST40	-20 - +40°C	6000040
MiL-CST200	0 - 200°C	60000200
MiL-CST300	50 - 300°C	60000300

Other temperature regulators or capillary pipe - thermostats on request.



Electronic temperature regulator MiL-EC200



Electronic temperature regulator series MiL-RD1000



Electronic temperature regulator series MiL-RD1053



Regulator- and limiter combination MiL-RD3000

MiL Heating Systems
Großer Sand 4
D-76698 Ubstadt-Weiher

Phone + 49 (0) 72 51 - 93247 - 0
Fax + 49 (0) 72 51 - 93247 - 29

E-Mail: info@isoheat.de
Internet: www.isoheat.de