

Quality products

ISOHEAT®

Electronical regulator-combination

series MiL-RD4011

EExi



Description:

In case of a failure temperature

This electronic microprocessor-controlled temperature regulator-limiter combination only can be install in Ex-free Zone. With inbuilt zener barrier for sensor input you can connect with a intrinsically safe sensor for Ex-zone.

Features:

- temperature regulators and limiter in one case
- stable table- und wall housing with transparent cover
- very flexible by PID-optimisation
- two displays for shown set and actual temperature value
- 2-pole main switch illuminated
- operation via press function-key
- parameter level settings
- input sensors: PT-100 or thermocouple
- temperature range 0 to 1200°C
- switching power up to 16 A
- changeable controller modul
- regulator deactivate at too high temperature

Technical data

MiL-RD4011

nominal voltage	230 V AC - 50/60 Hz
nominal current	16 A
switching power	3650 W
sensor input	2 x PT 100 to zener barrier, blue marking
temperature range	0 - 1200°C
accuracy	0,5 %
data security	EEPROM
EMV compatibility	EN 61326
protection class	I
system of protection	IP 65
ambient temperature	0 - 50°C
main cable	2,5 m with standard plug
dimension	198 x 212 x 162 x mm (w x h x d)

Order data

type	heating and sensor connection	switching power W	order-no.
MiL-RD4011	screw clamps	3650	61004011

Accessories

controller modul	Typ MiL-ST48	order-no. 61001200
------------------	--------------	--------------------



Electronic temperature regulator MiL-EC200



Electronic temperature regulator series MiL-RD1000



Electronic temperature regulator series MiL-RD2000



Regulator- and limiter combination MiL-RD3000

MiL Heating Systems
Großer Sand 4
D-76698 Ubstadt-Weiher

Phone + 49 (0) 72 51 - 93247 - 0
Fax + 49 (0) 72 51 - 93247 - 29

E-Mail: info@isoheat.de
Internet: www.isoheat.de