

Quality products

**ISOHEAT**®

## Bottom heater

### series MiL-HBD-200 and MiL-HBD-500

for temperatures up to 200°C / 500°C



#### Description:

Connection-ready, stable bottom heater, design for standard 200l-barrel.

This bottom heater can use in combination with our barrel heater for a shorter heating time. The design with stainless steel metal sheet guaranteed a heavy-duty construction as also stability under hard operational conditions.

With the integrated temperature regulation it may can regulate a temperature up to 200°C or 500°C.

#### Features:

- faster heating time
- no additional insulation necessary
- low surface load
- stable, robust construction
- high-quality stainless-steel construction

## Technical data

## MiL-HBD-200

voltage	230 V AC
power	see order data
dimension	Ø 510 x 85 mm
material	stainless steel
protection class	I
protection system	water-jet proof to IP 65
temperature controller	capillary controller 0 – 200°C
max. heating temperature	200°C
length main-cable	2,0 m with schuko-plug

## Technical data

## MiL-HBD-500

voltage	230 V AC
power	see order data
dimension	Ø 510 x 85 mm
material	stainless steel
protection class	I
protection system	water-jet proof to IP 65
temperature controller	capillary controller 0-500°C
max. heating temperature	500°C
length main-cable	2,0 m with schuko-plug

## Order data

type	power W	order.-no.
MiL-HBD-200	1150	51000300
MiL-HBD-500	2000	51000305

Other dimensions, voltages and performances - available on request



Drum heating jacket  
MiL-HJD-250S-450



Drum heating mat  
MiL-HMD-200



Drum band heater MiL-SMF

MiL Heating Systems  
Großer Sand 4  
D-76698 Ubstadt-Weiher

Phone + 49 (0) 72 51 - 93247 - 0  
Fax + 49 (0) 72 51 - 93247 - 29

E-Mail: [info@isoheat.de](mailto:info@isoheat.de)  
Internet: [www.isoheat.de](http://www.isoheat.de)