




ISOHEAT®



High Tech Engineering

Silicate-insulated heating cable

MIL-HC-H

Up to 900°C



Application examples:

- Consistently high performance
- High operating temperatures
- Small winding radius
- Very flexible
- **Not** protected against moisture
- **without** protective conductor braiding
- Pump and valve heating
- Pipe trace heating
- Tank heating
- Temperature control of machine parts
- Etc.

Technical data:

Outer sheath	Silicate-insulated
Nominal voltage	Up to 500 V AC
Rated power	Approx. 150 W/m
Heating cable dimensions	Ø 5,5 – 6,5 mm
Minimum bending radius	> 10 mm
Laying distance	> 6 mm
Protection class	0
Protection type	IP 20
Max. heatsealing band temperature	900°C
Cold ends	2 x 1,5 m standard (other lengths possible)

Order data

Length	Power	Item no.
0,6 m	90 W	12040005
1,0 m	150 W	12040010
1,5 m	250 W	12040015
2,0 m	350 W	12040020
3,0 m	500 W	12040030
4,0 m	700 W	12040040
5,0 m	850 W	12040050



Other lengths, nominal voltages and power ratings available on request

You can find further information and suitable accessories on our website: www.isoheat.de

Do you have any questions or need a quote?

Contact us at: office@isoheat.de



ISOHEAT GmbH
Großer Sand 4
D-76698 Ubstadt-Weiher

Tel.: +49 (0) 72 51 - 93247-0
Fax +49 (0) 72 51 - 93247-29

E-Mail: info@isoheat.de
Internet: www.isoheat.de