




ISOHEAT®



High Tech Engineering

PTFE-insulated heating cable

MIL-HC-PS

Up to 260°C



- Splash-proof
- Easy to install
- Very flexible
- Very long lengths possible
- Inexpensive
- **With** protective conductor braiding

Application examples:

- Pump and valve heating
- Pipe trace heating
- Tank heating
- Tempering of machine parts
- Etc.

Technical data:

| | |
|-----------------------------------|---|
| Outer sheath | PTFE-insulated |
| Nominal voltage | Up to 500 V AC |
| Rated power | approx. 20 W/m |
| Heating cable dimensions | Ø 3,0 – 5,0 mm |
| Minimum bending radius | > 10 mm |
| Laying distance | > 5 mm |
| Protection class | I |
| Protection type | IP 64 |
| Max. heatsealing band temperature | 260°C |
| Cold ends | 2 x 1,5 m standard (other lengths possible) |

Order data

| Length | Power | Item no. |
|--------|-------|----------|
| 1,8 m | 48 W | 20000018 |
| 3,0 m | 60 W | 20000030 |
| 5,1 m | 104 W | 20000050 |
| 7,2 m | 142 W | 20000072 |
| 11,0 m | 220 W | 20000110 |
| 17,0 m | 340 W | 20000170 |
| 23,0 m | 485 W | 20000230 |



Other lengths, nominal voltages and power ratings available on request

You can find further information and suitable accessories on our website: www.isoheat.de

Do you have any questions or need a quote?

Contact us at: office@isoheat.de



ISOHEAT GmbH
Großer Sand 4
D-76698 Ubstadt-Weiher

Tel.: +49 (0) 72 51 - 93247-0
Fax +49 (0) 72 51 - 93247-29

E-Mail: info@isoheat.de
Internet: www.isoheat.de