



ISOHEAT®



High Tech Engineering

PTFE-insulated heating cable

MIL-HC-P

Up to 260°C



Application examples:

- Splash-proof
- Easy to install
- Very flexible
- Very long lengths possible
- Inexpensive
- **Without** protective conductor braiding
- Pump and valve heating
- Pipe trace heating
- Tank heating
- Tempering of machine parts
- Etc.

Technical data:

Outer sheath	PTFE-insulated
Nominal voltage	Up to 50 V AC
Rated power	approx. 20 W/m
Heating cable dimensions	Ø 2,5 – 3,0 mm
Minimum bending radius	> 6 mm
Laying distance	> 3 mm
Protection class	Safety extra-low voltage
Protection type	IP 64
Max. heatsealing band temperature	260°C
Cold ends	2 x 1,5 m standard (other lengths possible)

Other lengths, nominal voltages and power ratings available on request



You can find further information and suitable accessories on our website: www.isoheat.de

Do you have any questions or need a quote?

Contact us at: office@isoheat.de



ISOHEAT GmbH

Großer Sand 4
D-76698 Ubstadt-Weiher

Tel.: +49 (0) 72 51 - 93247-0
Fax +49 (0) 72 51 - 93247-29

E-Mail: info@isoheat.de
Internet: www.isoheat.de