




# ISOHEAT®



## High Tech Engineering

### Heating mat with PTFE-insulated heating conductor

#### MIL-HPG-250

Up to 250°C



- Simple assembly and disassembly
- Wide variety of geometric shapes possible
- Cutouts can be considered
- Permanently integrated temperature sensor

## Technical data:

Nominal voltage	Up to 500 V AC
Rated power	Process-dependent
Outer jacket	Glass fiber with PTFE, PUR silicone or aluminium coating
Inner jacket	Glass fiber
Heatsealing band	PTFE-insulated resistance element
Mounting type	Hooks and loop tape, eyelets or Velcro
Protection class	I
Protection type	IP64
Temperature sensor (permanently installed)	Pt100 or thermocouple - according to customer specification
Max. temperature	250°C
Mains connection cable (silicone-insulated)	customised



You can find further information and suitable accessories on our website: [www.isoheat.de](http://www.isoheat.de)

Do you have any questions or need a quote?

Contact us at: [office@isoheat.de](mailto:office@isoheat.de)



**ISOHEAT GmbH**  
Großer Sand 4  
D-76698 Ubstadt-Weiher

Tel.: +49 (0) 72 51 - 93247-0  
Fax +49 (0) 72 51 - 93247-29

E-Mail: [info@isoheat.de](mailto:info@isoheat.de)  
Internet: [www.isoheat.de](http://www.isoheat.de)