




# ISOHEAT®



## High Tech Engineering

### Glass fibre insulated heating tape

#### MIL-HT-BS30

Up to 450°C



- High output per meter
- High operating temperature
- Wide-area heat transfer
- **Not** protected against moisture
- **With** protective conductor braiding inside

#### Application examples:

- Frost protection
- Temperature control of pipework and valves
- Temperature control of machine parts and containers
- Etc.

## Technical data:

Outer jacket	Glass fiber insulated
Nominal voltage	Up to 500 V AC
Rated power	approx. 250 W/m
Dimensions	35 x 5 mm
Minimum bending radius	> 15 mm
Laying distance	> 10 mm
Protection class	I
Protection type	IP 20
Max. heatsealing band temperature	450°C
Main connection cable	1,0 m long

## Order data

Length	Power	Item no.
0,5 m	125 W	13000005
1,0 m	250 W	13000010
1,5 m	375 W	13000015
2,0 m	500 W	13000020
3,0 m	750 W	13000030
4,0 m	1000 W	13000040
5,0 m	1250 W	13000050



**Other lengths, nominal voltages and power ratings available on request**

You can find further information and suitable accessories on our website: [www.isoheat.de](http://www.isoheat.de)

Do you have any questions or need a quote?

Contact us at: [office@isoheat.de](mailto:office@isoheat.de)



**ISOHEAT GmbH**  
Großer Sand 4  
D-76698 Ubstadt-Weiher

Tel.: +49 (0) 72 51 - 93247-0  
Fax +49 (0) 72 51 - 93247-29

E-Mail: [info@isoheat.de](mailto:info@isoheat.de)  
Internet: [www.isoheat.de](http://www.isoheat.de)