




# ISOHEAT®



## High Tech Engineering

### PTFE-insulated heating tape

### MIL-HT-CN

Up to 260°C



- Splash-proof
- Wide-area heat transfer
- Very flexible
- **With** protective conductor braiding
- **With** M20 x 1.5 screw connection

#### Application examples :

- Frost protection
- Temperature control of pipework and valves
- Temperature control of machine parts and containers
- Etc.

## Technical data:

Outer jacket	Metal mesh
Nominal voltage	Up to 500 V AC
Rated power	approx. 35 W/m or approx. 50 W/m
Dimensions	8,5 x 6 mm
Minimum bending radius	> 15 mm
Laying distance	> 10 mm
Protection class	I
Protection type	IP 64
Max. heatsealing band temperature	260°C
Main connection cable	1,0 m long with M20 x 1.5 screw connection

## Order data 35W/m

Length	Power	Item no.
1,9 m	67 W	11000019
2,7 m	95 W	11000027
3,9 m	137 W	11000039



## Order data 50W/m

Length	Power	Item no.
2,3 m	115 W	11100020
4,2 m	210 W	11100040
7,6 m	380 W	11100080

**Other lengths, nominal voltages and power ratings available on request**

You can find further information and suitable accessories on our website: [www.isoheat.de](http://www.isoheat.de)

Do you have any questions or need a quote?

Contact us at: [office@isoheat.de](mailto:office@isoheat.de)



**ISOHEAT GmbH**  
Großer Sand 4  
D-76698 Ubstadt-Weiher

Tel.: +49 (0) 72 51 - 93247-0  
Fax +49 (0) 72 51 - 93247-29

E-Mail: [info@isoheat.de](mailto:info@isoheat.de)  
Internet: [www.isoheat.de](http://www.isoheat.de)