




ISOHEAT®



High Tech Engineering

PTFE-insulated heating tape MIL-HT-PSG

Up to 260°C



- Splash-proof
- Wide-area heat transfer
- Very flexible
- **with** protective conductor braiding inside

Application examples:

- Frost protection
- Temperature control of pipework
- Temperature control of machine parts and containers
- Etc.

Technical data:

Outer jacket	PTFE-insulated
Nominal voltage	bis 500 V AC
Rated power	approx. 50 W/m
Dimensions	25 x 5 mm
Minimum bending radius	> 20 mm
Laying distance	> 10 mm
Protection class	I
Protection type	IP 64
Max. heatsealing band temperature	260°C
Main connection cable	1,0 m long

Order data

Length	Power	Item no.
1,0 m	44 W	12010010
2,3 m	115 W	12010023
3,5 m	150 W	12010035
5,5 m	230 W	12010055
780 m	360 W	12010080
11,0 m	510 W	12010110
14,0 m	570 W	12010140



Other lengths, nominal voltages and power ratings available on request

You can find further information and suitable accessories on our website: www.isoheat.de

Do you have any questions or need a quote?

Contact us at: office@isoheat.de



ISOHEAT GmbH
Großer Sand 4
D-76698 Ubstadt-Weiher

Tel.: +49 (0) 72 51 - 93247-0
Fax +49 (0) 72 51 - 93247-29

E-Mail: info@isoheat.de
Internet: www.isoheat.de