



ISOHEAT®



High Tech Engineering

PTFE-insulated heating tape MIL-HT-PSS

Up to 260°C



Application examples :

- Splash-proof
- Wide-area heat transfer
- Very flexible
- Small bending radius
- **With** protective conductor braiding
- Frost protection
- Temperature control of pipework and valves
- Temperature control of machine parts and containers
- Etc.

Technical data:

Outer jacket	Metal mesh
Nominal voltage	Up to 500 V AC
Rated power	approx. 50 W/m
Dimensions	18 x 4 mm
Minimum bending radius	> 5 mm
Laying distance	> 10 mm
Protection class	I
Protection type	IP 64
Max. heatsealing band temperature	260°C
Main connection cable	1,0 m long

Order data

Length	Power	Item no.
0,6 m	75 W	15000006
1,2 m	110 W	15000012
1,5 m	175 W	15000015
2,0 m	220 W	15000020
2,5 m	260 W	15000025
3,0 m	340 W	15000030
4,5 m	430 W	15000045



Other lengths, nominal voltages and power ratings available on request

You can find further information and suitable accessories on our website: www.isoheat.de

Do you have any questions or need a quote?

Contact us at: office@isoheat.de



ISOHEAT GmbH

Großer Sand 4
D-76698 Ubstadt-Weiher

Tel.: +49 (0) 72 51 - 93247-0
Fax +49 (0) 72 51 - 93247-29

E-Mail: info@isoheat.de
Internet: www.isoheat.de